Fusion Interleaf Flap Disc

The combination of a premium coated abrasive layer over non-woven surface conditioning material is what makes Fusion a superior flap disc. Fusion easily blends and finishes welds in one operation. Grain size is calibrated in order to match a #4 finish.

METALS

Stainless steel - Aluminum - Mild steel - Brass

PRODUCT FEATURES

Blends and finishes stainless steel in one step Matches a satin finish Very controlled weld grinding High quality finish

APPLICATIONS

Blend corner welds on stainless steel railings Blend small TIG welds on stainless steel kitchen equipment

SPECIFICATIONS

Grain TypesAluminum Oxide

Grain Sizes

Coarse, Medium, Very Fine

AVAILABILITY

DIAMETER X ARBOR		MAX	OPTIMUM	CRS	MED	VFINE
inch	mm	RPM	RPM			
4-1/2 x 7/8	115 x 22.2	13,300	2,700-5,000	894000	894001	894002
4-1/2 x 5/8-11	N/A	13,300	2,700-5,000	894003	894004	894005
5 x 7/8	125 x 22.2	12,200	2,500-4,500	894006	894007	894008
5 x 5/8-11	N/A	12,200	2,500-4,500	894009	894010	894011

TIP

While working on stainless steel with a satin finish, run this product in the same direction as the scratches to match the grain.









800-225-8182 www.rexcut.com info@rexcut.com

youtube.com/user/rexcutabrasives twitter.com/rexcut linkedin.com/company/rexcut facebook.com/rexcut



Improve Your Daily Grind